



VRM-AX7115A

Product Datasheet

Overview:

The **VRM-AX7115A** is a 1U 15" LCD with Keyboard Drawer and KVM Switch.

Features:

- **LCD:** 15" TFT active matrix panel
- **Resolution:** 1024 x 768 @ 16,777,144 colors
- **Contrast Ratio:** 350:1
- **Brightness:** 250 (max)
- **Compatibility:** VGA, SVGA (RGB analog)
- **Scan Frequency:** 31.47- 60KHz (H), 43-85Hz (V)
- **KVM Switch:** 8 sets of auto switch with built-in manual and auto-scan functions
- **Dimensions (WxDxH):** 19" (482.6mm) x 20.28" (515.1mm) x 1.7" (44mm)



Specifications:

- **LCD:** 15" TFT active matrix panel
- **Display Size:** 304.1 x 228.1mm
- **Pixel Pitch:** 0.297 x 0.297mm
- **Display Module:** VGA 640 x 350 (70Hz); VGA 720 x 400 (70Hz); VGA 640 x 480 (60/72/75Hz); SVGA 800 x 600 (60/72/75Hz); XGA 1024 x 768 (60/70/75Hz); Mac. 832 x 624 (75Hz)
- **Max. Resolution:** 1024 x 768
- **Contrast Ratio:** 350:1
- **Brightness:** 250 (max)
- **Response Time:** 15mS (rising), 10mS (falling)
- **Display Colors:** 16M (dithering)
- **Input Signal Video:** R.G.B. analog 0.7V Peak-to-Peak
- **Sync:** TTL positive or negative
- **Signal Connector:** 15-pin mini D-sub
- **Front Control:** Power switch, menu, select (up,down), adjust (+,-)
- **OSD:** Auto-adjustment, contrast, brightness, clock, phase, H-position, V-position, color temperature, load default
- **Plug & Play:** DDC1/2B
- **Keyboard:** 105 keys
- **Mouse:** Touch pad PS/2 mouse
- **Power:** Universal 90-240V, 12V/35W
- **Dimensions:** 19"W x 20.28"H x 1.7"D
- **Weight:** 18Kg
- **Certifications:** FCC-A, CE, UL

Ordering options:

- **VRM-AX7115AT:** 1U rackmount 15" LCD with keyboard drawer
- **VRM-AX7115AT-8:** 1U rackmount 15" LCD with keyboard drawer & 8-port KVM switch