

**Features:**

- 3U rack/enclosure 30HP, shielded, ready for installation of 1 x system slot CompactPCI CPU card 3U/4HP (without companion board) or 8HP (with companion board), 3 x peripheral slot CPCI cards 3U/4HP, equipped with 1 x CPCI PSU 3U/10HP, according to IEEE 1101.10, shock-and-vibration according to IEC 61587-1 and Bahn-Norm BN411002/BN411003.
- Dimensions: 170mm (W) x 132mm (H) x 205mm (D) without accessories
- CompactPCI Bus:
 - 1 x P1/P2 system slot, right side (red card rails)
 - 3 x P1 peripheral slots
 - CompactPCI 32-bit, +5V VIO (+3.3V VIO on request)
 - 1 x M connector for PSU slot, left side
- PSU (AC Version):
 - Removable, 3U/10THP, permanently short circuit proof, over-voltage protection primary/secondary
 - Ambient, temperature -25°C ... +70°C (derating 2%/K above 50°C), protected against overheating
 - Line input 90-138VAC/187-264VAC 50/60Hz (changing automatically), input connector IEC320/C5
 - Outputs +5V/8A, +33.V/10A, M24/8 connector matching the backplane, SELV according to EN 60950
- Accessories (optional):
 - Fan unit
 - Wall mount brackets
 - Bottom mount brackets
 - Tip up feet

Ordering options:

- VRM-CRB-1: Rack 3U/30HP, with CPCI backplane, with removable Power Supply 70W 115/230VAC
- VRM-CRB-2: Similar to VRM-CRB-1, except with removable Power Supply 70W 24VDC
- VRM-CRB-5: Kit tip up feet (for desk top systems)
- VRM-CRB-6: Kit wall mount brackets
- VRM-CRB-7: Kit bottom mount brackets
- VRM-CRB-8: Fan unit
- VRM-CC2-1: CPU Board 4HP with ULV Celeron® 400MHz processor
- VRM-CC6-3: Option I/O mezzanine module (companion board) 4HP for VRM-CC2
- VRM-CC6-8: Option hard disk 2.5" (mounted on VRM-CC6)
- VRM-CC9-1R: CPU board 4HP with ULV Celeron® M 600 MHz processor
- VRM-CC9-2R: CPU board 4HP with ULV Celeron® M 1GHz processor
- VRM-CC9-3R: CPU board 4HP with LV Pentium® M 1.4GHz processor
- VRM-CC9-5R: CPU board 4HP with Pentium® M 1.8GHz processor
- VRM-CC9-6R: CPU board 4HP with Pentium® M 2.0 GHz processor
- VRM-CCA-1R: I/O mezzanine module (companion board) 4HP for VRM-CC9
- VRM-CCA-8-HD: Hard disk 2.5" (mounted on VRM-CCA)
- VRM-CCB-1R: I/O mezzanine module (companion board) for 4HP for VRM-CC9
- VRM-CCB-8-HD: Hard disk 2.5" (mounted on VRM-CCB)